



# AKRON DISPERSIONS, INC.

## MATERIAL SAFETY DATA SHEET

Page 1 of 3

### SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: **Bostex 417**

CHEMICAL NAME: Aqueous Mixture of N,N'-Diphenylguanidine(CAS# 102-06-7), Sodium Salts of Polymerized Alkyl naphthalenesulfonic Acid(CAS# 9084-06-4/36290-04-7)

MANUFACTURER: Akron Dispersions, Inc.  
3291 Sawmill Road P.O. Box 4195  
Akron, Ohio 44321

TELEPHONE NUMBER: (330)666-0045

EMERGENCY TELEPHONE NUMBER: (330)666-0045

FAX: (330)666-7842

### SECTION 2 HAZARDOUS INGREDIENT INFORMATION

N,N'-Diphenylguanidine(CAS# 102-06-7)  
Paraffin Oil(CAS# 8012-95-1/72623-86-0): 0.4 - 1.2%  
Formaldehyde(CAS# 50-00-0): <0.00045%  
Naphthalene(CAS# 91-20-3): <0.00018%  
Quinoline(CAS# 91-22-5): <0.0018%

### SECTION 3 HAZARDS IDENTIFICATION

Health Hazards(Acute and Chronic): May cause irritation to eyes, skin, and mucous membranes. Cases of skin sensitization have been reported when incorporated in rubber articles. May contain <0.00045% Formaldehyde, <0.00018% Naphthalene, and <0.0018% Quinoline, known to the State of California to cause cancer.

HMIS: Health-2 Flammability-0 Reactivity-0 Personal Protection-B

### SECTION 4 FIRST AID MEASURES

Eye Contact: Flush with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

Skin Contact: Wash affected area with soap and water. Consult a physician if irritation persists.

Inhalation: Remove to fresh air. If breathing is difficult, seek medical attention.

Ingestion: Give 2-4 glasses water. Get immediate medical attention.

### SECTION 5 FIRE & EXPLOSION HAZARD

Flashpoint: N/D Flammable Limits: N/D

General Hazard: Wear MSHA-NIOSH approved Self-Contained Breathing Apparatus

Extinguishing Media: CO<sub>2</sub>, Dry Chemical, Waterspray, Foam

Decomposition Products Under Fire Conditions: Oxides of Carbon, Nitrogen, Sulfur, and Sodium

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

Steps To Be Taken In Case Material Is Released Or Spilled: Absorb with inert material. Sweep, vacuum, or shovel into appropriate container.

**SECTION 7 HANDLING AND STORAGE**

Storage: Store in a cool, dry area.

Storage Temperature: Above 32°F

**SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**

OSHA Regulation 29CFR1910.1000 requires the following PEL Limits: N/D

The ACGIH recommends the following Occupational Exposure Limit: N/D

Personal Protection: Gloves and Goggles recommended

Ventilation: Local Exhaust

**SECTION 9 TYPICAL PHYSICAL & CHEMICAL PROPERTIES**

Product Appearance: White to Off-White Liquid

Boiling Point(°F): 212

Vapor Pressure(@150°C): N/A

Vapor Density: N/A

Solubility in Water: Miscible

pH: 9.5-11.0

Freezing Point(°F): 32

Specific Gravity(Approx.): N/D

% Volatile by Volume: 60%

Evaporation Rate: N/A

**SECTION 10 STABILITY AND REACTIVITY DATA**

Stability: Stable

Conditions To Avoid Instability: None Known

Materials And Conditions To Avoid Incompatibility: Strong Oxidizers

Hazardous Decomposition Products: Oxides of Carbon, Nitrogen, Sulfur, and Sodium

Hazardous Polymerization: Will Not Occur

Conditions To Avoid Hazardous Polymerization: None Known

**SECTION 11 TOXICOLOGICAL INFORMATION**

Carcinogenicity(NTP/IARC/OSHA): None. May contain <0.00045% Formaldehyde, <0.00018% Naphthalene, and <0.0018% Quinoline, known to the State of California to cause cancer.

**SECTION 12 ECOLOGICAL INFORMATION**

Not determined

**SECTION 13 DISPOSAL**

Waste Disposal Method: Dispose per Local, State, and Federal Regulations

**SECTION 14 TRANSPORT INFORMATION**

DOT: Not a DOT controlled material(United States).

**SECTION 15 REGULATORY INFORMATION**

TSCA: All ingredients of this product appear on the TSCA Inventory  
SARA Title III-Section 313: This product does not contain a toxic chemical in excess of 1% of the mixture(0.1% if a listed carcinogen).

**SECTION 16 OTHER INFORMATION**

Prepared By: D. Hunsicker  
Date: January 8, 2010

The information in this MSDS was compiled from sources which we believe are accurate and reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness. It is the user's responsibility to determine the suitability of any material for a specific purpose and adopt such safety precautions as may be necessary. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with the handling, storage, use, or disposal of this product.